

C253250S

Switch disconnecter, ComPacT NSX250NA, 3 poles, fixed, thermal current Ith 250A



Main

Range	ComPacT new generation
Product name	ComPacT NSX new generation
Device short name	NSX250NA
Product or component type	Switch disconnecter
Device application	Distribution
Poles description	3P
[Ith] conventional free air thermal current	250 A at 50 °C
[Ie] rated operational current	AC-22A: 250 A AC 50/60 Hz 220...690 V AC-23A: 250 A AC 50/60 Hz 220...690 V DC-22A: 250 A DC 250 V 1 pole DC-22A: 250 A DC 500 V 2 poles in series DC-23A: 250 A DC 250 V 1 pole DC-23A: 250 A DC 500 V 2 poles in series DC-22A: 250 A DC 750 V 3 poles in series DC-23A: 250 A DC 750 V 3 poles in series
[Ue] rated operational voltage	690 V AC 50/60 Hz 750 V DC 3 poles in series 500 V DC 2 poles in series 250 V DC 1 pole
Network type	AC DC
Suitability for isolation	Yes conforming to EN/IEC 60947-3
Utilisation category	AC-22A AC-23A DC-22A DC-23A
Breaking capacity code	NA
Contact position indicator	Yes
Visible break	No
Mounting mode	Fixed
[Icw] rated short-time withstand current	3.5 kA during 1 s 3.5 kA during 3 s 1.35 kA during 20 s
[Icm] rated short-circuit making capacity	330 kA with upstream protection circuit breaker 4.9 kA switch-disconnector alone
Control type	Toggle
[Ui] rated insulation voltage	800 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV

Complementary

Mounting support	Backplate
Upside connection	Front
Downside connection	Front
Connection pitch	35 mm
Mechanical durability	20000 cycles

Electrical durability	AC-22A: 15000 cycles 440 V AC 50/60 Hz In/2 AC-23A: 15000 cycles 440 V AC 50/60 Hz In/2 AC-22A: 7500 cycles 440 V AC 50/60 Hz In AC-23A: 7500 cycles 440 V AC 50/60 Hz In AC-22A: 6000 cycles 690 V AC 50/60 Hz In/2 AC-23A: 6000 cycles 690 V AC 50/60 Hz In/2 AC-22A: 3000 cycles 690 V AC 50/60 Hz In AC-23A: 3000 cycles 690 V AC 50/60 Hz In DC-22A: 10000 cycles 250 V DC In/2 (1 pole) DC-23A: 10000 cycles 250 V DC In/2 (1 pole) DC-22A: 5000 cycles 500 V DC In (2 poles in series) DC-23A: 5000 cycles 500 V DC In (2 poles in series)
Width (W)	105 mm
Height (H)	161 mm
Depth (D)	86 mm
Net weight	1.8 kg
Standards	EN/IEC 60947-1 EN/IEC 60947-3
Product certifications	CE[RETURN]EAC[RETURN]CCC

Environment

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Electrical shock protection class	Class II
Pollution degree	3 conforming to IEC 60664-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.2 cm
Package 1 Width	11.5 cm
Package 1 Length	19.3 cm
Package 1 Weight	1.996 kg
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	14.346 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
PVC free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov