Empty enclosure for switchgear

AKi-TE 216



AKi-TE 216

Empty enclosure for switchgear

Productnumber: 78921601
Dimensions: 300 x 300 x 132 mm

Switch disconnector enclosure with external actuation, lockable, IP65 (when using the corresponding cable infeeds), 1 x load disconnector switch 160A, 3-pole switching, Cage-type terminal 10 - 70 mm², PE/N terminal 2 x 50 mm², with IP54 attachment bushes, with insulating seals

with transparent cover

Technical Data

electrical characteristics

Rated operating voltage AC:	690 V
Protection class:	II
Type of protection:	IP54/IP65
Rated current:	160 A
UL Type Rating:	not specified

Colours

Base unit colour:	grey
Cover colour:	transparent

Dimensions

Width:	300 mm
Length:	300 mm
Height:	132 mm
Weight:	3 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability:	850 °C (EN 60695-2-11)

mechanical properties

Impact strength:	IK08
Sealable:	yes

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C

Ambient conditions

Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Installation location:	protected outdoor areas

Sales Information

EAN:	4013902885619
ETIM Class:	EC000249
Custom tariff number:	85369095
Minimum order quantity:	1


Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced

Accessories

79300401 - AK ABL-ES - External fixing lugs

Cable gland


2x M20
2x M32/M40
1x M40/M50/
M63
2x M32/M40/
M50
2x M32/M40/
M50
2x M20
2x M32/M40
1x M40/M50/
M63