
Distribution board

# GTi 2 VS-KT-t



## GTi 2 VS-KT-t

**Distribution board**

CUSTOMIZABLE

Productnumber: 02100201
Dimensions: 320 x 320 x 179 mm

Module enclosure, 1-row, standard version sealable, with 35 mm standard rails for installing a selective main switch, incl. 2 single pole HA terminals 25/16 mm² for N and PE, masking and labelling strips, 3 x enclosure connectors (GGV)

**with transparent hinged door**



# Technical Data

## electrical characteristics

| | |
|---|---|
| Rated insulation voltage AC: | 400 V |
| Protection class: | II |
| Type of protection: | IP65 |
| Number of modules: | 14 |

## Colours

| | |
|---|---|
| Base unit colour: | grey |
| Cover colour: | transparent |

## Dimensions

| | |
|---|---|
| Width: | 320 mm |
| Length: | 320 mm |
| Height: | 179 mm |
| Inner height: | 157 mm |
| Weight: | 2.913 kg |

## Material characteristics

| | |
|---|---|
| UV-resistant: | yes |
| Halogen free: | yes |
| Flammability class according with UL94: | V2 |
| Glow-wire flammability: | 960 °C (EN 60695-2-11) |

## mechanical properties

| | |
|---|---|
| Type of fastening: | Surface mounting |
| Impact strength: | IK08 |
| Cover screw torque: | 2.5 Nm |
| Stackable: | yes |

## Ambient conditions

| | |
|---|---|
| max. relative humidity 25°C: | 95 % |

## Ambient conditions

| | |
|---|---|
| max. relative humidity 40°C: | 50 % |
| Min. ambient temperature: | -25 °C |
| Max. ambient temperature: | 40 °C |
| 24h ambient temperature: | 35 °C |
| Installation location: | protected outdoor areas |

## Sales Information

| | |
|---|---|
| EAN: | 4013902902842 |
| ETIM Class: | EC000214 |
| Custom tariff number: | 85369095 |
| Minimum order quantity: | 1 |

## Material

| | |
|---|---|
| Base unit material: | Polycarbonate |
| Cover material: | Polycarbonate |
| Sealing material: | Polyurethane |
| Cover screw material: | Polyamide, glass-fibre reinforced |

## Accessories

07251201 - GFS 12-m - Flange set