

**VP HEX M25 PA6 GY****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Similar to illustration**

In addition to cable glands for a wide range of applications, the product portfolio is rounded off by plugs, pressure compensation elements, adaptors and the corresponding accessories such as locknuts, sealing rings, flat washers and earthing rings.

**General ordering data**

|            |                                                                        |
|------------|------------------------------------------------------------------------|
| Version    | Blanking plugs, in closed state, M 25 x 1.5, 15 mm, Polyamide 6 (PA 6) |
| Order No.  | <a href="#">2715760000</a>                                             |
| Type       | VP HEX M25 PA6 GY                                                      |
| GTIN (EAN) | 4050118805420                                                          |
| Qty.       | 25 pc(s).                                                              |

## VP HEX M25 PA6 GY

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                      |        |                      |            |
|----------------------|--------|----------------------|------------|
| Height               | 5.8 mm | Height (inches)      | 0.228 inch |
| Width                | 28 mm  | Width (inches)       | 1.102 inch |
| Length               | 15 mm  | Length (inches)      | 0.591 inch |
| Diameter             | 32 mm  | Wall thickness, min. | 0.5 mm     |
| Wall thickness, max. | 14 mm  | Net weight           | 0.006 g    |

## Temperatures

|                       |                  |
|-----------------------|------------------|
| Operating temperature | -20 °C... 100 °C |
|-----------------------|------------------|

## General information

|                                   |                             |                                   |                              |
|-----------------------------------|-----------------------------|-----------------------------------|------------------------------|
| Cable glands                      | metric                      | Diameter of sealing ring          | 25 mm                        |
| External thread                   | M 25 x 1.5                  | Halogen                           | No                           |
| Length of thread                  | 15 mm                       | Material                          | Polyamide 6 (PA 6)           |
| Operating temperature range, max. | 100 °C                      | Operating temperature range, min. | -20 °C                       |
| Pitch of thread                   | 1.5 mm                      | Protection degree                 | IP65, IP68 - 5 bar (30 min.) |
| Standards                         | in accordance with UL94 V-2 | Tightening torque                 | 2.5 Nm                       |
| UL 94 flammability rating         | V-2                         |                                   |                              |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000451    | ETIM 7.0    | EC000451    |
| ETIM 8.0    | EC000451    | ETIM 9.0    | EC000451    |
| ETIM 10.0   | EC000451    | ECLASS 9.0  | 27-14-44-25 |
| ECLASS 9.1  | 27-14-44-33 | ECLASS 10.0 | 27-14-44-25 |
| ECLASS 11.0 | 27-14-44-25 | ECLASS 12.0 | 27-14-08-05 |
| ECLASS 13.0 | 27-14-08-05 | ECLASS 14.0 | 27-14-08-05 |
| ECLASS 15.0 | 27-14-08-05 |             |             |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|            |                                          |
|------------|------------------------------------------|
| Catalogues | <a href="#">Catalogues in PDF-format</a> |
|------------|------------------------------------------|