



Main

Range of product	Acti9
Product name	Acti9 iCM
Product or component type	Selector switch
Device short name	iCMB
Device application	Electrical circuit control
Contacts type and composition	2 C/O
[Ue] rated operational voltage	415 V AC 50/60 Hz
Standards	VDE 0660 part 107 IEC 60947-3 EN 60947-3 UL

Complementary

[Ie] rated operational current	10 A
Maximum operating voltage	440 V
Control type	Rotary handle 3 positions
Marking	1 - 0 - 2
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	4
Height	60 mm
Width	36 mm
Depth	75 mm
Net weight	58 g
Colour	White
Mechanical durability	1000000 cycles
Electrical durability	AC-21A: 200000 cycles
Connections - terminals	Jumper terminals 1.5 mm ²
Wire stripping length	9 mm for downside connection
Tightening torque	1 N.m downside

Environment




IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-20...55 °C
Ambient air temperature for storage	-25...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.3 cm
Package 1 Width	7.6 cm
Package 1 Length	8.4 cm
Package 1 Weight	74.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	80

Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	6.407 kg

Offer Sustainability

REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------