



Hoofd

Range	TeSys Tesys deca
Device short name	LAD4
Product or component type	Onderdrukkingsmodule
Compatibiliteit product	3P LC1D40A...D80A 4P LC1DT60A...DT80A

Complementair

Montagezone	Voorkant
Mounting mode	Met klemmen
Ontstoringstechnologie	RC-circuit
Spanning stuurkring	380...415 V AC
Maximum piekspanning	3 Uc
Net weight	0,02 kg
Colour	Donkergrijs

Omgeving

Standards	IEC 60947-5-1 EN 60947-5-1 CSA C22.2 Nr 60947-5-1 UL 60947-5-1 GB/T 14048,5
Product certifications	UL[RETURN]CSA
IP beschermingsgraad	IP2x conform aan IEC 60529
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...80 °C

Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2,000 cm
Package 1 Width	3,000 cm
Package 1 Length	6,000 cm
Package 1 Weight	21,000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	6,300 cm
Package 2 Width	7,300 cm
Package 2 Length	12,000 cm
Package 2 Weight	230,000 g
Unit Type of Package 3	S01
Number of Units in Package 3	100

Package 3 Height	15,000 cm
Package 3 Width	15,000 cm
Package 3 Length	40,000 cm
Package 3 Weight	2,458 kg

Duurzaamheid van het aanbod

Duurzaamheids status van het aanbod	Green Premium product
REACH-regelgeving	REACH-verklaring
REACH vrij van SVHC	Ja
EU-richtlijn RoHS	Voldoet EU-verklaring RoHS
Vrij van giftige zware metalen	Ja
Kwikkvrij	Ja
RoHS-regulering China	RoHS-verklaring China
Informatie over RoHS-vrijstelling	Ja
Milieu Profiel	Milieuprofiel Van Het Product
Circulair Profiel	Geen specifieke recycling vereist
WEEE	Het product moet op markten van de Europese Unie worden afgevoerd volgens specifieke afvalinzamelingsregels en mag nooit in een gewone vuilnisbak terechtkomen.

contractuele waarborg

Garantie	18 months
----------	-----------