

PV XSTU04 BUOEVO2-C250**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The Y cable is used for the parallel connection of several strings in a PV system, e.g. for splitting a line in front of an inverter.

The cables are available in different connection variants.

General ordering data

Version	Photovoltaics, Y connector
Order No.	3018480250
Type	PV XSTU04 BUOEVO2-C250
GTIN (EAN)	4099986930384
Qty.	1 pc(s).

PV XSTU04 BUOEVO2-C250

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight 1,000 g

PV cable harnessing

PV cable version	Cable side	left
	Number	1
	Cable length	2,500 mm
	Cable colour	black
	Cable cross section	4 mm ²
	Inline fuse integrated	No
	Version of cable end [In-Block]	free conductor end
	Connector version	MC4-Evo 2
	Type of plug-in contact	female
	Cable side	right
Rated DC voltage		1,500 V
Wire cross-section		4 mm ²

Electrical characteristics

Rated DC voltage 1,500 V

Classifications

ETIM 6.0	EC001576	ETIM 7.0	EC001576
ETIM 8.0	EC001576	ETIM 9.0	EC001576
ETIM 10.0	EC001576	ECLASS 9.0	27-06-04-02
ECLASS 9.1	27-06-91-90	ECLASS 10.0	27-06-04-02
ECLASS 11.0	27-06-04-02	ECLASS 12.0	27-06-04-02
ECLASS 13.0	27-06-04-02	ECLASS 14.0	27-06-04-02
ECLASS 15.0	27-06-04-02		

Downloads

Catalogues [Catalogues in PDF-format](#)

PV XSTU04 BUOEVO2-C250

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

