

**PAC-RX3I-HE20-V5-5M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Similar to illustration

The pre-assembled PAC cables establish an electrical and logical connection between the PLC and the PLC interfaces. These cables consist of the following components:

- Manufacturer's PLC connector.
- Multi-pole LIYY or LY YCY cable (shielded) with a cross-section of 0.14 mm<sup>2</sup> or 0.25 mm<sup>2</sup>.
- Flat cable connector, SUB-D or RSV, for connection to the interface.

The cables are tested automatically for their continuity and insulation to guarantee the functionality for which they have been designed.

**General ordering data**

|            |                                                            |
|------------|------------------------------------------------------------|
| Version    | Pre-assembled cable, PAC, Cable LiYY, 0.25 mm <sup>2</sup> |
| Order No.  | <a href="#">2680680050</a>                                 |
| Type       | PAC-RX3I-HE20-V5-5M                                        |
| GTIN (EAN) | 4099986639706                                              |
| Qty.       | 1 pc(s).                                                   |

**PAC-RX3I-HE20-V5-5M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |       |
|------------|-------|
| Net weight | 624 g |
|------------|-------|

**Temperatures**

|                     |             |                       |            |
|---------------------|-------------|-----------------------|------------|
| Storage temperature | -10...60 °C | Operating temperature | 10...50 °C |
|---------------------|-------------|-----------------------|------------|

**General Data**

|                    |                         |                     |                              |
|--------------------|-------------------------|---------------------|------------------------------|
| Cable              | Cable LiYY              | Cable length        | 5 m                          |
| Connector PLC side | GEFANUC IC694ACC311 20P | Interface connector | FLAT CABLE CONECTOR HE10 20P |
| Material           | PVC                     | Outer diameter      | 8.6 ± 1 mm                   |
| Wire cross-section | 0.25 mm <sup>2</sup>    |                     |                              |

**Electrical Data**

|                       |                   |                                             |           |
|-----------------------|-------------------|---------------------------------------------|-----------|
| Capacity wire / wires | 300 pF/m          | Permissible current strength per path, max. | 1 A       |
| Rated voltage         | ≤ 60 Vdc ≤ 25 Vac | Resistance                                  | ≤ 80 mΩ/m |
| Total current, max.   | 3 A               |                                             |           |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000237    | ETIM 7.0    | EC000237    |
| ETIM 8.0    | EC000237    | ETIM 9.0    | EC000237    |
| ETIM 10.0   | EC000237    | ECLASS 9.0  | 27-24-22-20 |
| ECLASS 9.1  | 27-24-22-20 | ECLASS 10.0 | 27-24-22-20 |
| ECLASS 11.0 | 27-24-22-20 | ECLASS 12.0 | 27-24-22-20 |
| ECLASS 13.0 | 27-24-22-20 | ECLASS 14.0 | 27-24-22-20 |
| ECLASS 15.0 | 27-24-22-20 |             |             |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|