



Hoofd

Range	Masterpact
Product or component type	Apparaattoepassing
Omschrijving toepassing	Afschakelfout WFC
Bereik compatibiliteit	MASTERPACT MTZ1 automatisch MASTERPACT MTZ2 automatisch MASTERPACT MTZ3 automatisch
Compatibiliteit product	besturingsunit Micrologic 2.0 X[RETURN] besturingsunit Micrologic 3.0X[RETURN] besturingsunit Micrologic 5.0 X[RETURN] besturingsunit Micrologic 6.0 X[RETURN] besturingsunit Micrologic 7.0 X[RETURN] besturingsunit MicroLogic 2.0 Xi[RETURN] besturingsunit MicroLogic 3.0 Xi[RETURN] besturingsunit MicroLogic 5.0 Xi[RETURN] besturingsunit MicroLogic 6.0 Xi[RETURN] besturingsunit MicroLogic 7.0 Xi
Service omschrijving	Sampling period of 512 micro seconds in case of trip of LSI or G protection Allows to log automatically five cycles of phase and neutral currents Records the following status: circuit breaker open/closed/trip and ZSI signals Display one cycle before the fault and 4 cycles after
Service voordelen	Help to understand the potential damage on the installation Support analysis of global behaviour of the circuit breaker in the power system Help to understand the nature and gravity of the fault (amplitude and duration)
Energiebeheer	Diagnostiek en onderhoud ,Crisismanagement (optie)

Complementair

Naam software	EcoStruxure Power Commission
---------------	------------------------------

Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0,001 g

Duurzaamheid van het aanbod

REACH-regelgeving	 REACH-verklaring
EU-richtlijn RoHS	Voltoet aan vrijstellingen
Kwivrij	Ja
RoHS-regulering China	 RoHS-verklaring China
Informatie over RoHS-vrijstelling	 Ja