



Main

Range of product	Canalis
Product name	KS
Product or component type	Bracket
Product compatibility	KS
Fixing device mounting	Suspended on threaded rod Wall mounting
Maximum load	135 kg
Quantity per set	Set of 10

Complementary

Accessory / separate part categor	Fixing accessory
[Ie] rated operational current	1000.0 A
Width	151 mm
Depth	30 mm
Height	181.5 mm
Net weight	400 g

Environment

Standards	IEC 60439-2 IEC 61439-6
-----------	----------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.0 cm
Package 1 Width	19.0 cm
Package 1 Length	31.0 cm
Package 1 Weight	365.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	18.5 cm
Package 2 Width	16.5 cm
Package 2 Length	32.5 cm
Package 2 Weight	3.86 kg
Unit Type of Package 3	P06
Number of Units in Package 3	300
Package 3 Height	80.0 cm
Package 3 Width	80.0 cm
Package 3 Length	60.0 cm
Package 3 Weight	128.0 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------