932 A Screwdriver for slotted screws, 1.6 x 9 x 150 mm



EAN:	4013288018045	**Size:**	262x40x40 mm
Part number:	05018268001	**Weight:**	205 g
Article number:	932 A	**Country of origin:**	CZ
		Customs tariff number:	82054000

- Chiseldriver for fastening, chiselling and loosening
- Hexagonal blade extending through the handle
- Multi-component Kraftform handle for fast and ergonomic screwdriving
- Impact cap and bolster for the transfer of higher torque
- The Wera Black Point tip offers an exact fit and optimum corrosion protection

Wera chiseldriver for screwdriving, chiseling, mortising and slackening stuck screws. With multi-component Kraftform handle for fast and smooth work. Kraftform Plus: Hard handle zones for high working speeds, while soft handle zones guarantee a high torque transfer. The pound-thru hexagonal blade made of premium bit material ensures power transmission without loss even at hammer blows. Tough tempered material to prevent the blade from splintering or breaking. With integrated impact cap to increase service life and reduce risk of splintering. Higher torques can be transmitted with open-end or ring spanners using the integrated hexagon bolster. The Wera Black Point tip and a sophisticated hardening process guarantee a long usability for the tip, increased corrosion protection and exact fitting accuracy. With hexagon anti-roll protection to avoid bits from rolling away annoyingly in the workplace.

KRAFTFORM ERGONOMICS

IMPACT CAP

HEXAGON BLADE

POUND-THRU BLADE

HEXAGON BOLSTER

BLACK POINT

ANTI ROLL-OFF

Web link
https://www.wera.de/en/05018268001

Wera - 932 A
05018268001 - 4013288018045

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de



Screwdrivers are often misused as chisels. This can be dangerous. The chiseldriver is the solution when not only screwdriving is required. For fastening, chiselling and loosening seized screws. Wera chiseldriver: the screwdriver whenever the going gets tough!

Integrated impact cap



An integrated impact cap lengthens the service life and reduces the danger of splintering. Nevertheless, always wear protective goggles.

Pound-thru blade



A hexagon blade made out of high-quality bit material extends right through the handle - thereby ensuring full transfer of force, even when struck with a hammer. The ductile tempered material prevents the blade from splintering or breaking.

Integrated hex bolster



Greater torque can be transferred by fitting an open-jaw or ring spanner over the integrated hex bolster.

Wera Black Point tip




The Wera Black Point tip and a refined hardening process ensure long service life of the tip, improved corrosion protection and an exact fit.

Kraftform



The basic idea for the prototype of the Kraftform handle - that the hand should dictate the design - has, right through to today, proved to be correct. In cooperation with the internationally recognised Fraunhofer IAO Institute, Wera developed a screwdriver handle designed to match the shape of the human hand as long ago as the 1960s. After a long development phase, the Wera Kraftform handle was launched to the market in 1968. It has been optimised through the years with new technologies, but has kept its proven shape. After all, the human hand has not changed either.

Rapid hand repositioning



The hard materials used for the handle ensure rapid hand repositioning without any danger of the skin "sticking" to the handle. The surrounding hard zones with large diameters glide like wheels through the hand.

Non-roll feature



The hexagonal non-roll feature prevents any rolling away at the workplace.

Web link
https://www.wera.de/en/05018268001

Wera - 932 A
05018268001 - 4013288018045

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Further versions in this product family:

	 mm	 mm	 mm	 mm	 mm	 mm	 inch	 inch
05018260001[1),2),3)]	0.6	3.5	4	-	80	81	9/64"	3 1/8"
05018262001	0.8	4.5	5	8	90	98	0.178"	3 1/2"
05018264001	1.0	5.5	6	10	100	105	7/32"	4"
05018266001	1.2	7.0	6	10	125	105	9/32"	5"
05018268001	**1.6**	**9.0**	**8**	**13**	**150**	**112**	**11/32"**	**6"**
05018270001	1.6	10.0	8	13	175	112	3/8"	7"
05018272001[4)]	2.0	12.0	10	16	200	117	1/2"	8"
05018274001[4)]	2.5	14.0	10	16	250	117	9/16"	10"

1) No pound-thru blade
2) No impact cap
3) No hexagon bolster
4) Kraftform handle, one-component

Web link
https://www.wera.de/en/05018268001

Wera - 932 A
05018268001 - 4013288018045

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de