


High-power LED streetlight with cover, frame, and pole attachment in EN AB 46100 die-cast aluminium with low copper content, with polyester powder coating. Suitable for installation both on top of the pole and offset, with 5° pitch adjustment. Opening and closing system with integrated front handle. Closure fabricated in tempered flat glass (thickness 4 mm). Cable input via PG13.5. Safety switch. Cable plate in PA6.6+PV. Printed Circuit Board (PCB) in metal core. Metallic PC optic system. Common mode surge protection up to 10 kV. Operational up to 50°C ambient temperature but with reduction of the supply current as indicated in the Instruction Manual.

| GENERAL INFORMATION                     |                                                   | OPTIC AND ILLUMINATING FEATURES     |                                                  |
|-----------------------------------------|---------------------------------------------------|-------------------------------------|--------------------------------------------------|
| Context                                 | Street and parking lighting                       | Optic                               | WIDE                                             |
| Luminaire                               | LED Road Equipment                                | Unified Glare Rating                | G*4 - ULOR = 0                                   |
| Application                             | External                                          | Lumen output (lm)                   | 12800                                            |
| Unique digital code (Datamatrix)        | Currently not present                             | Efficacy (lm/W)                     | 115                                              |
| Colour                                  | Graphite grey                                     | Colour temperature                  | 3000 K                                           |
| Type of light source                    | LED                                               | Colour Rendering Index              | CRI>70                                           |
| System power                            | 111 W @ 1A                                        | Standard Deviation Colour Matching  | SDCM = 5                                         |
| LED Lifetime                            | L90B10(Tq25°C)>115.000h; L90B10 (Tq40°C)=115.000h | Photobiological Risk Class          | RG0                                              |
| Weight (kg)                             | 8                                                 | Standard                            | EN 60598-2-3, EN 60598-1 IEC/TR 62778            |
| Warranty                                | 5 years                                           | ELETRICAL AND LIGHTING FEATURES     |                                                  |
| Stocking temperature                    | -                                                 | Supply voltage                      | 220 - 240 V                                      |
| Operating temperature                   | -25 +40 °C                                        | Rated frequency (Hz)                | 50 / 60                                          |
| MATERIALS                               |                                                   | Driver failure rate                 | F10=100.000h Tq25°C/75.000h Tq40°C               |
| Body                                    | Die-cast aluminium                                | Driver                              | Included                                         |
| Shield type                             | 4mm thick flat tempered glass                     | Overvoltage protection              | DM 10KV / CM 10KV                                |
| Optic                                   | Silver PVD aluminium reflector                    | Control System                      | Dimmable 1-10 V                                  |
| Gasket                                  | Anti-aging silicone                               | INSTALLATION AND MAINTENANCE        |                                                  |
| Locking Hook                            | Integrated front handle                           | Mounting and installation           | Pole Head - Outreach                             |
| External screw                          | Stainless steel                                   | Tilt                                | -20° ÷ +10° side bracket - -10° ÷ +20° pole head |
| Colour                                  | Powder coating                                    | Wiring                              | Isolating switch                                 |
| STANDARDS AND APPROVALS                 |                                                   | Fixing                              | Pole Head - Outreach                             |
| Classification                          | -                                                 | Light source replaceability         | By professional                                  |
| Device with reduced surface temperature | -                                                 | Controlgear replaceability          | By professional                                  |
| DIN 18032-3 certification               | Not available                                     | Driver Box                          | Built-in                                         |
| IPEA                                    | -                                                 | Maximum surface exposed to the wind | 0.19 m²                                          |
| Insulation class                        | II                                                |                                     | -                                                |
| IP degree                               | IP66                                              |                                     | -                                                |
| Mechanical resistance                   | IK08                                              |                                     | -                                                |
| Glow Wire Test                          | -                                                 |                                     | -                                                |

### DIMENSIONAL



### PHOTOMETRIC DISTRIBUTION

### TECHNICAL SYMBOLOGY



IP  
IP66

IK  
IK08

GWT  
-



## Product Data Sheet

# GWR5213M30K

40 CDI Range

### STANDARDS/APPROVALS

