LV432642

Standard motor mechanism module MT400/630, ComPacT NSX400/630, 380/415VAC 50/60Hz





Main

Device short name	MT400/630
Product or component type	Motor mechanism
Device application	Automatic spring charging
Range compatibility	ComPacT new generation ComPacT NSX400 new generation ComPacT new generation ComPacT NSX630 new generation ComPact ComPacT NSX DC new generation NSX400 DC ComPact ComPacT NSX DC new generation NSX630 DC
Control type	Standard
[Uc] control circuit voltage	380415 V AC 50 Hz
Circuit breaker mounting mode	Fixed
Circuit breaker frame rated current	630 A 400 A

Complementary

Complementary		
Control signal type	Impulse Maintained	
Circuit breaker response time	< 700 ms open < 80 ms closed	
Maximum operating frequency	4 per minute	
Maximum power consumption in VA	500 VA closing 500 VA opening	
Locking options description	Padlocking in OFF position 1 to 3 padlocks Ø 5 to Ø 8	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	19.6 cm	
Package 1 Width	17.0 cm	
Package 1 Length	17.0 cm	
Package 1 Weight	3.142 kg	
Unit Type of Package 2	S04	
Number of Units in Package 2	6	
Package 2 Height	30.0 cm	
Package 2 Width	40.0 cm	
Package 2 Length	60.0 cm	
Package 2 Weight	19.456 kg	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent or and is not to be used for determining suitability or inhability of these products for specific user applications. It is the dourn aren in integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months