



Hoofd

Product or component type	Hulpcontact
Device short name	PF (SF)
Bereik compatibiliteit	Masterpact Masterpact NT Masterpact Masterpact NW
Samenstelling signaleringscontacten	1 NO/NC

Complementair

Type hulpcontacten	Standaard
Mounting mode	Vast
Onderbrekingsvermogen (A)	AC-12: 5 A at 480 V AC 50/60 Hz AC-12: 3 A at 690 V AC 50/60 Hz AC-12: 5 A at 240/380 V AC 50/60 Hz DC-12: 0,15 A at 250 V DC DC-12: 3 A at 24/48 V DC DC-12: 0,3 A at 125 V DC
Minimale belasting	100 mA bij 24 V

Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1,3 cm
Package 1 Width	4,7 cm
Package 1 Length	6,5 cm
Package 1 Weight	36,0 g

Duurzaamheid van het aanbod

REACH-regelgeving	REACH-verklaring
REACH vrij van SVHC	Ja
EU-richtlijn RoHS	Voldoet pro-actief (Product valt niet onder de EU RoHS juridische scope)
Kwkvrij	Ja
RoHS-regulering China	RoHS-verklaring China
Informatie over RoHS-vrijstelling	Ja

contractuele waarborg

Garantie	18 months
----------	-----------