

I-FAST products are JOINON's DC fast-charging solutions ideal for charging all types of electric vehicles equipped with high-voltage systems in private or public high-rotation parking lots, highways and service areas. The offer consists of wallboxes up to 30 kW and stations up to 180 kW. They feature an elegant design and finishes that make them an urban and extra-urban furnishing product, with a graphic display for a better User Experience and use of services for the EV Driver user.

Power specification - AC input		-	Environmental	-
Input voltage	3Φ 380 ÷ 415 Vac	Operating temperature	-30℃ ÷ +50 ℃	
AC input connection	3P+N+PE (Wye configuration), TN/TT	Humidity	5% ÷ 95% RH, Non-Condensing	
Max input current	3 Φ 86A	Altitude	≤ 2.000 m	
Frequency	50 Hz / 60 Hz	IP degree	IP55	
Power factor	> 0.99	Mechanical resistance	IK10 (not including screen & RFID module)	
Efficiency	>94%	Cooling method	Fan cooling	
Power specification - DC output		-	Mechanical	-
Output voltage range	CCS2: 150 ÷ 950 Vdc	Dimension	700 mm x 330 mm x 1.800 mm	
Max output current	CCS2: 120A	Weight	235 kg	
Maximum output power	60 kW	Cable length	4 m	
Voltage/Current accuracy	±2%	Protection	-	
User interface & control		-	Input protection	OVP, OCP, OPP, OTP, UVP, RCD, SPD
Display	7" LCD	Output protection	SCP, OCP, OVP, LVP, OTP, IMD	
Push buttons	Operation Buttons / Emergency Stop Button	Regulation	-	
User Authentication	RFID: support ISO 14443A/B, ISO 15693, FeliCa Lite-S (RCS966), OCPP 1.6 JSON, QR Code, App	Safety	CE, CB	
Meter	AC MID Meter, Integrated DC Meter	Certificate	IEC 61851-1, IEC 61851-23, IEC 61851-21-2	
Communication	-	Charging interface	DIN 70121, ISO 15118-2	
External	Ethernet, Wi-Fi and 4G	Contactless Solution	-	
Internal	CAN bus / RS485	Payment terminal	No	

DIMENSIONAL

TECHNICAL SYMBOLOGY

IP

IK

IP55

IK10 (not including screen & RFID module)

STANDARDS/APPROVALS

UK
CA CE