



Hoofd

Range of product	Lexium Cobot
Product or component type	Collaborative robot
Maximum payload	12 kg
Operating radius	1327 mm
Positioning accuracy	+/- 0.02 mm
Degree of freedom	6
Programming	Graphical drag & drop
Teach-in device	Ipad ios app Android app

Complementair

Maximum speed	120°/S joint 1 +/- 360° 120°/S joint 2 -85, +265° 120°/S joint 3 +/- 175° 180°/S joint 4 -85, +265° 180°/S joint 5 +/- 360° 180°/s joint 6 +/- 360°
Nominale spanning	24 V
Aantal analoge ingangen	2
Aantal analoge ingangen	2
Aantal analoge ingangen	1
Maximale energieverbruik in W	500 W
Montagepositie	Eender welke positie
Type schroef	M8
Standards	GB 11291.1:2011 EN/ISO 10218-1:2011 EN 60204-1:2018 EN/ISO 12100:2010 EN/ISO 13849-1:2015 EN 61000-6-2:2005 EN 61000-6-4:2007+A1:2011 ISO 13849-1:2015 ISO 13849-2:2012 ISO 14644-1 ISO 9001:2015 UL 1740 ANSI/RIA R15.06 CAN/CSA Z434 NFPA 79 CAN/CSA C22.2 Nr. 24 REACH RoHS
Markering	CE KC TÜV
Materiaal	Aluminium
Base diameter	188 mm
Kabellengte	6 m
Net weight	41 kg

Milieu

IP-beschermingsgraad	IP54
Ambient air temperature for operation	0...50 °C

Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	53,500 cm
Package 1 Width	58,500 cm
Package 1 Length	91,000 cm
Package 1 Weight	48,200 kg

Duurzaamheid van het aanbod

Duurzaamheids status van het aanbod	Green Premium product
REACH-regelgeving	 REACH-verklaring
REACH vrij van SVHC	Ja
EU-richtlijn RoHS	Voldoet pro-actief (Product valt niet onder de EU RoHS juridische scope)
Kwikvrij	Ja
RoHS-regulering China	 RoHS-verklaring China
Informatie over RoHS-vrijstelling	 Ja
Milieu Profiel	 Milieuprofiel Van Het Product
Circulair Profiel	 Informatie Over Einde Levensduur