

Junction box

Abox SLK-4²/w



Abox SLK-4²/w

Junction box

Productnumber: 80417001

Dimensions: 102 x 102 x 57 mm

Junction box, protection class IP66, nominal cross-section 4 mm², U_i=450 V AC, certified by VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), DLG (Ammonia resistance), self-sealing, soft insertion membranes, M20/M25, sealing range 4 - 21 mm, (1 rear, 10 side), internal fixing points, with screwless terminals and clamp holders, for standard indoor and protected outdoor installations

white, I_n=32 A, with 5 floor-fixed, screwless 3-wire terminals, Wago 221-413 - 4 mm², clampable cross-sections per pole: 3 x 0.2 to 4 mm² rigid Cu and 3 x 0.14 to 4 mm² flexible Cu



Technical Data

electrical characteristics

Rated insulation voltage AC:	450 V
Rated insulation voltage DC:	450 V
Min. conductor cross section:	0,2 mm ²
Max. conductor cross section:	4 mm ²
Protection class:	II
Type of protection:	IP66
Rated current:	32 A
Terminal type:	screwless
Number of poles:	5

Colours

Base unit colour:	white
Cover colour:	white

Dimensions

Width:	102 mm
Length:	102 mm
Height:	57 mm
Inner length:	90 mm
Inner width:	90 mm
Inner height:	49 mm
Weight:	0.1501 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability:	750 °C (EN 60695-2-11)

mechanical properties

for sealing range min:	4 mm
for sealing range max:	21 mm
Impact strength:	IK07
Sealable:	yes
Cover screw torque:	1.2 Nm
Type of fastening:	Wall/ceiling mounting
Fastening:	internal fixing points

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	55 °C
24h ambient temperature:	35 °C
Installation location:	protected outdoor areas

Sales Information

EAN:	4013902703227
ETIM Class:	EC002600
Custom tariff number:	85369095
Minimum order quantity:	1

Material

Base unit material:	Polypropylene
Cover material:	Polypropylene
Entry material:	Thermoplastic elastomer
Sealing material:	Thermoplastic elastomer
Cover screw material:	Stainless steel 1.4567 (V2A)

Certificates

Test mark: VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))

Test mark: DLG (Ammonia resistance)

Accessories

[26011601 - DMS M16/w - Double-membrane seals](#)

[26012001 - DMS M20/w - Double-membrane seals](#)

[26012501 - DMS M25/w - Double-membrane seals](#)

[89500101 - Abox PST 025-100 - Sealing kit](#)

[22741601 - KVR M16-MGM - Cable gland](#)

[22742101 - KVR M20-GDB/MGM - Cable gland](#)

[22742001 - KVR M20-MGM - Cable gland](#)

[22742501 - KVR M25-MGM - Cable gland](#)

[89601001 - MABF 65-1 - Mast/pipe fixing set](#)

[89602901 - KTB 1-100 - Cable tray fastening](#)

Cable gland

