PEN terminal

GN 0



GN 0

PEN terminal

Productnumber: 07600201
Dimensions: 25,7 x 125 x 43 mm

for mounting plate

N terminal NH 00 (clamp connection) for CU conductors 1x (1.5-70)rm / 2x 50rm, for mounting plate

Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Rated operating voltage AC:	690 V
Rated operating voltage DC:	440 V
Rated current:	160 A
Number of poles:	1
shockproof:	No
Connection 1: Connection type:	Screws
Connection 1: Clamping points per pole:	2
Connection 1: Suitable for Cu conductors:	1
Connection 1: Suitable for Al conductors:	1
Connection 1: Connectable conductor cross-section, fine-wire with ferrule (min):	1.5 mm²
Connection 1: Connectable conductor cross-section, fine-wire with ferrule (max):	70 mm²
Connection 1: Connectable conductor cross-section, stranded (min):	1.5 mm²
Connection 1:Connectable conductor cross-section, stranded (max):	70 mm²

Dimensions

Width:	25.7 mm
Length:	125 mm
Height:	43 mm
Weight:	0.14 kg

Material characteristics

Glow-wire flammability:	960 °C (EN 60695-2-11)

mechanical properties

Connection 1: Tightening moment:	3 Nm

Sales Information

EAN:	4013902340743

Sales Information

ETIM Class:	EC002498
Custom tariff number:	85369010
Minimum order quantity:	1

Material

Insulating body material:	Thermoplastic

Accessories

07670001 - KP NH 00 - Prism terminal