Large conduit box

U 120 K GRO-2



U 120 K GRO-2

Large conduit box

Productnumber: 97371201
Dimensions: 74 x 74 x 122 mm

Large conduit box , for ceiling slab thickness up to 6.5 cm, with M5 threaded bushing (load capacity 10 kg) to hold ceiling hook, protection class IP30, rated insulation voltage: 400V AC, Halogen free

adhesive fixing or nail installation, membrane for perforation, sealing range M16 - M32

Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V
Type of protection:	IP30
Suitable for:	Concrete construction
UL Type Rating:	not specified

Colours

Cover colour:	other

Dimensions

Width:	74 mm
Length:	74 mm
Height:	122 mm
Weight:	0.071 kg

Material characteristics

Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability:	650 °C (EN 60695-2-11)

mechanical properties

Type of fastening:	adhesive fixing or nail installation

Ambient conditions

max. relative humidity 25°C:	- %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Sales Information

EAN:	4013902030491
ETIM Class:	EC002601
Custom tariff number:	39269097
Minimum order quantity:	1

Material

Base unit material:	Polypropylene
Cover material:	Polypropylene

Accessories

97822301 - IBT LZA-23 - Hole punch

97821801 - IBT LZA-18 - Hole punch

97820001 - IBT LZA-OE - Hole punch

19599501 - LFR - Stepped drill

97022501 - RVB 25 - Conduit coupling

97924001 - NAS-AL - IBT Accessories

97924201 - NA-AL - IBT Accessories

97924301 - NA-AL/gl - IBT Accessories

97910001 - VD 75 - sealing plate

97912101 - DH 115-M5 - ceiling hook

92510001 - HW VD-67 - sealing plate

Cable gland

