



Main

| | |
|---|---|
| Range of product | TransferPacT |
| Product or component type | Automatic transfer switch |
| Device application | Change source of supply |
| Poles description | 3P |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Downside connection | Screwed |
| Mounting mode | Fixed |
| Upside connection | Screwed |
| Contact position indicator | Yes |
| [Icm] rated short-circuit making capacity | 15 kA switch-disconnector alone 400 V AC at 50 Hz 75 kA with upstream protection circuit breaker 400 V AC at 50 Hz |
| Suitability for isolation | Yes |

Complementary

| | |
|---|------------------------------------|
| Transfer switch class | PC |
| Number of contact position | 3 |
| Signal contacts composition | 1 NO + 2 NC 1 NC + 2 NO 2 NO |
| Utilization category | AC-33B |
| [Ue] rated operational voltage | 400 V AC 50/60 Hz |
| Control type | Rotary knob Selector switch |
| Operating mode | Automatic Manual |
| Mounting support | Plate DIN rail |
| Locking options description | Padlock in OFF position |
| Rated duty | Uninterrupted |
| [Ui] rated insulation voltage | Switch: 800 V Controller: 500 V |
| [Uimp] rated impulse withstand voltage | Switch: 6 kV Controller: 6 kV |
| [Ie] rated operational current | 32 A |
| Mechanical interlocking | With mechanical interlocking |
| Mechanical durability | 8000 cycles |
| Connection pitch | 18 mm |
| [Icw] rated short-time withstand current | 5 kA during 0.1 s |
| Height | 145 mm |
| Width | 306 mm |
| Depth | 94 mm |
| Net weight | 3.4 kg |
| [Ith] conventional free air thermal current | 32 A at 60 °C |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 60947-6-1 |
| Product certifications | CE[RETURN]CB[RETURN]CCC |
| IP degree of protection | Front face: IP40 auto mode Inside the enclosure: IP20 manual mode |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -35...85 °C |
| Pollution degree | 3 |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 14.000 cm |
| Package 1 Width | 21.000 cm |
| Package 1 Length | 37.000 cm |
| Package 1 Weight | 4.118 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |